
SAFETY EYEWEAR

Uvex Seismic Sealed Eyewear

WITH READING MAGNIFIERS

Delivering unmatched protection against impact, wind, dust and debris, Uvex Seismic offers a range of diopter strengths for workers needing increased magnification for reading, inspection, and other fine detail work. The wraparound design provides exceptional coverage while precise placement of the magnifiers allow for distortion-free vision. Uvex Seismic Reading

Magnifiers: powerful eyewear for today's demanding work environments.



Features

- Superior coverage ideal for dirty, high-particulate work environments such as grinding, chipping, shaving and sanding.
- Available in Clear with Uvextra[™] Anti-fog coating and three diopter strengths: +1.5, +2.0 and +2.5 magnifications.
- Superior antifog coating, coupled with top and bottom indirect ventilation, minimizes fogging to keep workers safe and comfortable all day.
- Flexible design can be worn with temples or with headband as conditions change.
- Soft, flexible nasal pads conform to a variety of facial profiles and minimize slippage.
- Soft, high-quality face cushioning and padded temple tips offer all-day comfort.
- Highly adjustable flame-resistant headband provides excellent fit.
- Replaceable flame-resistant, cushion-lined subframe and headband extend the life of the eyewear.
- High impact protection certified to ANSI Z87+ (High Impact) and CSA Z94.3 standards. (ANSI-certified for use with and without cushion-lined frame).

ORDERING INFORMATION						
EYEWEA	R LENS TINT	FRAME	LENS COATING	MAGNIFICATION	UPC CODE	
S0661X	Clear	Black	Uvextra Anti-fog	+1.5	603390128455	
S0662X	Clear	Black	Uvextra Anti-fog	+2.0	603390128462	
S0663X	Clear	Black	Uvextra Anti-fog	+2.5	603390128479	
ACCESSORIES ITEM# DESCRIPTION UPC CODE						
S6249	Headband Replacement (Flame-Resistant)				603390125317	

Cushion-Lined Subframe Replacement (Flame-Resistant)

Packaging Information (Eyewear) Ind. Box, 10/stocker, 200/case Case Weight: 38 lbs. Case Dimensions: 29" x 15" x 24"

S6250

Packaging information (Subframe) Ind. bag, 10/stocker, 200/case Case Weight: 4.75 lbs. Case Dimensions: 7.6" x 6.3" x 2"

Packaging information (Headband) Ind. bag, 10/stocker, 200/case Case Weight: 12.7 lbs. Case Dimensions: 6.7" x 6.6" x 3.4"

603390125324

Diopter Chart

Hold chart 14 inches from face to figure diopter strength	Diopter
If this line is difficult to read, use	+1.5
If this line is difficult to read, use	+2.0
If this line is difficult to read, use	+2.5



FOR MORE INFORMATION, CONTACT:

Sperian Protection Americas, Inc. 900 Douglas Pike Smithfield, RI 02917-1874 (800) 430-5490 www.uvex.us